





SECW475 PANEL CROSS SECTION (TYP.)

TYP. CROSS SECTION

GENERAL NOTES:

- The contractor shall confirm alignment of the ChampionWall with the grade shown on the contract plans.
- 2. Contractor shall be responsible for determining the layout and location of the cross-sections in accordance with the owner's requirements and contract plans. At all transitions the taller wall section post size and spacing shall be maintained until the shorter section obtained.
- 3. The contractor will provide quality control programs to ensure that the finished product meets the specifications
- 4. Overall plumbness of wall 1"/10-ft of wall height.
- 5. Overall plumbness of piling 1"/20' of exposed height.
- 6. Sufficient drainage to be designed, installed, and connected to storm water management system by others.
- 7. Contractor shall locate all underground utilities to avoid conflict prior to drilling foundations.
- 8. Contractor shall complete subgrade requirements per site specific Geotechnical Report and contract plans provided by others prior to wall construction.
- 9. Designed for a 3-sec gust wind speed equal to XX mph per ASCE 7-XX Risk Category I.
- 10. Foundation design is in accordance to Geotechnical Report NO. XXX-XXXXX provided by XXX.
- 11. All concrete shall have minimum compressive strength of f'c = 3000 PSI.
- 12. Minimum foundation size and depth is in accordance with ASTM F567.
- 13. All hardware shall be Hot Dipped Galvanized Steel.
- 14. All pipe shall be ASTM F 1083 Schedule 40, Grade XX ksi and hot-dipped galvanized.
- 15. SECW475 panel color shall be CHALLENGER GREEN / DEFENDER BLUE / ELIMINATOR GRAY
- 16. Unistrut Wale shall be P1000T with the following properties:
- 16.1. Guage = 12 (Minimum)
- 16.2. Ry = 33KSI
- 16.3. E = 29,000 ksi
- 16.4. Area = 0.55 in^2
- 16.4.1. $lx = 0.185 in^4$
- 16.4.2. $ly = 0.236 in^4$
- 16.4.3. $Sx = 0.202 \text{ in}^3$ 16.4.4. $Sy = 0.290 \text{ in}^3$



SportsEdge ChampionWall System Information

B.W.M. B.W.M. BY: XXX

DATE: 08.01.23

B.W.M. BRAWING NUMBER: SECW475

DISCLAIMER: The customer and the customer's architects, engineers, consultants and other professionals are completely responsible for the selection, installation, and maintenance of any product purchased from ABT, and EXCEPT AS EXPRESSLY PROVIDED IN ABT'S STANDARD WARRANTIES, ABT MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMER'S APPLICATION. Copies of ABT's standard warranties are available upon

Proprietary right of ABT, Inc. are included in the information disclosed herein. The recipient, by accepting this document, agrees that neither this document nor the information disclosed herein nor any part thereof shall be copied, reproduced or transferred to others for manufacturing or for any other purpose except as specifically authorized in writing by ABT, Inc.