



Technical Data Sheet

COMPOSITION

DiamondWall Outfield Wall components are manufactured from Poly Vinyl Chloride (PVC)

PHYSICAL & PERFORMANCE CHARACTERISTICS

Base Material	Virgin Polyvinyl Chloride (PVC)		
Color Layer Material	Acrylonitrile Styrene Acrylate (ASA)		
Overall Thickness	0.24	in	
Color Layer Thickness	0.003	in	
Weight	2.58	lbs/ft ²	
Density	86.2	lb/ft ³	
Tensile Strength	377	psi	
Panel Width Finished	12.0	in	
Panel Width O/A	13.4	in	
Min. Ambient Operating Temp.	32	°F	
ASTM 2440-18 Test Result	Pass		
Gmax (ASTM F1292) Avg.	63		
HIC (ASTM F1292) Avg.	249		
Warranty	20	Years	
Color choices -Wall	Monster Green	RAL 6005	
	All-Star Gray	RAL 7026	
	Stadium Blue	RAL 5010	
Back of all Wall Panels	Lt. Gray		
Color - StadiumGuard Cap	Yellow	RAL 1023	

Proprietary rights of SportsEdge are included in the information disclosed herein. The recipient, by accepting this document, agrees that neither this document nor the information disclosed herein nor any part thereof shall be copied, reproduced or transferred to others for manufacturing or for any other purpose except as specifically authorized in writing by SportsEdge.

Disclaimer: The customer and the customer's architects, engineers, consultants and other professionals are completely responsible for the selection, installation, and maintenance of any product purchased from SportsEdge, and EXCEPT AS EXPRESSLY PROVIDED IN SPORTSEGE STANDARD WARRANTIES, SPORTSEGE MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMER'S APPLICATION. Copies of SPORTSEGE standard warranties are available upon request.

