



Model SEF308R - Rotating Football Goal Specifications :

Ground Sleeve - 8" Schedule 40 Steel Pipe (8 5/8" OD X 0.322" Wall), Finish - uncoated

Rotating Offset Goose Neck - 6" Schedule 40 - 6063-T5 Aluminum Pipe (6 5/8" OD x 0.280" Wall)

Custom Designed 360° Rotation Section with Corrosion Resistant Stainless & Bronze Bearings,
180° Rotation Lockable Position, Installs in the Standard Ground Sleeve Assembly

Cross Bar - 6" Schedule 40 - 6061-T6 Aluminum Pipe (6 5/8" OD x 0.280" Wall)

Uprights - 4" OD x 0.125" Wall - 6061-T6 Aluminum Pipe

Finish - Powder Coated Yellow or White

Fasteners - Grade 5 - Zinc Plated Steel

2010 MODEL DESIGN

308R_specif-00
04/19/11

SportsEdge®

A Division of ABT, Inc.

P.O. Box 837 * 259 Murdock Road
Troutman, NC 28166
800-334-6057

Proprietary rights of ABT, Inc. are included in the information disclosed herein. The recipient, by accepting this document, agrees that neither this document nor the information disclosed herein nor any part thereof shall be copied, reproduced or transferred to others for manufacturing or for any other purpose except as specifically authorized in writing by ABT, Inc.

DISCLAIMER: The customer and the customer's architects, engineers, consultants and other professionals are completely responsible for the selection, installation, and maintenance of any product purchased from ABT, and EXCEPT AS EXPRESSLY PROVIDED IN ABT'S STANDARD WARRANTIES, ABT MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMER'S APPLICATION. Copies of ABT's standard warranties are available upon request.